

BTP-U80-II Budget Thermal Receipt Printer

Reliability at Reasonable Cost, Triple Interface



PRINTING: direct thermal, 180x180 dpi resolution, 72 mm width, 200 mm/s speed. **PAPER:** 80 mm thermal paper rolls with max. 83 mm diameter, also can print 58/70/76/82 mm width paper rolls. **CUTTER:** full or partial auto-cuts, tear-off for manual cuts. **ESC/POS:** command emulation supported. **FONTS:** 12x24 (42 chars/line max.) and 9x17 (56 chars/line max.) 95 Alphanumeric characters, 13 international sets, code pages downloadable into printer memory. **BARCODES:** most 1D barcodes including GS1 DataBar and 2D barcodes. **MEMORY:** 2M/4M flash (dependable to different font library), 512 KB for graphics, data buffer 64KB/4KB/45 bytes. **INTERFACES:** 3-in-1 (USB + Serial + Ethernet), cash drawer kick-out port. **POWERING:** via external power adaptor, input 100-240 VAC, 50-60 Hz, output 24V ± 5% VDC, 1.5A. **RELIABILITY:** ruggedized with steel frame inside, 150 km printouts, 1.5 million cuts, MCBF 60 million lines, MTBF 360K hours. **DETECTION:** LED/Buzzer signals for open top cover, paper end and near end, print head overheating, voltage and cutter errors. **DIMENSIONS:** 195x145x141 mm. **WEIGHT:** 1.45 kg. **SETTINGS:** via built-in menu by FEED button or by PC with Print Utility software. **DRIVERS:** Windows, OPOS, JavaPOS, Linux CUPS, MAC support. **EMC & CE:** approved.